



QuietMOD H/P-38 PANEL DESCRIPTION:

- PANEL IS 2" THICK WITH SOLID SKIN ON ONE SIDE AND A PERFORATED SKIN ON THE OTHER.
- ENTIRE PANEL IS CONSTRUCTED WITH "PAINT READY" GALVANNEAL A-60 STEEL WITH INTERNAL STIFFENERS EVERY 24" O.C.
- FACE SHEETS ARE SPOT WELDED TO THE PANEL FRAMING CHANNEL
- ALL STIFFENERS AND CHANNEL FRAMING ARE FORMED FROM A MINIMUM OF 18 GA. STEEL
- ACOUSTIC FILL IS NON-COMBUSTIBLE, SOUND ABSORBING FIBERGLASS OR MINERAL WOOL
- PRIME PAINTING OR FACTORY FINISH PAINTING IS AVAILABLE
- PANEL WEIGHS 4.7 lbs./sq.ft.

SOUND TRANSMISSION LOSS, dB

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QuietMOD H/P-38 PANEL	24	25	33	43	50	55	38

\*All testing conducted by Riverbank Acoustical Laboratories  
 \*All data in accordance with ASTM E90-99 and E413-87

SOUND ABSORPTION COEFFICIENTS

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	NRC
QuietMOD H/P-38 PANEL	0.26	0.53	1.00	1.03	0.97	1.02	0.90

\*All testing conducted by Riverbank Acoustical Laboratories  
 \*All data in accordance with ASTM C423-90a and E795-00

REVISIONS		DESCRIPTION	
DESCRIPTION	DATE	BY	CUSTOMER

  

DESCRIPTION	QuietMOD H/P-38 ACOUSTIC PANEL
CUSTOMER	
DRAWN BY	MAH
SCALE	
DATE	
DRAWING NO.	QM-HP-38
SHEET	

  

2001 Kelley Court, Libertyville, IL 60048  
 Phone: 847-843-0500  
 Fax: 847-843-0501  
 www.noisebarriers.com