



QuietMOD H/P-50 PANEL DESCRIPTION:

- PANEL IS 4" THICK WITH SOLID SKIN ON ONE SIDE AND A PERFORATED SKIN ON THE OTHER.
- ENTIRE PANEL IS CONSTRUCTED WITH "PAINT READY" GALVANNEAL A-60 STEEL WITH INTERNAL STIFFENERS EVERY 24" O.C.
- FACE SHEETS ARE SPOT WELDED TO THE PANEL FRAMING CHANNEL
- ALL STIFFENERS AND CHANNEL FRAMING ARE FORMED FROM A MINIMUM OF 18 GA. STEEL
- ACOUSTIC FILL IS NON-COMBUSTIBLE, SOUND ABSORBING FIBERGLASS OR MINERAL WOOL
- PRIME PAINTING OR FACTORY FINISH PAINTING IS AVAILABLE
- PANEL WEIGHS 10.4 lbs./sq.ft.

SOUND TRANSMISSION LOSS, dB

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	STC
QuietMOD H/P-50 PANEL	29	37	48	56	57	54	50

*All testing conducted by Riverbank Acoustical Laboratories
 *All data in accordance with ASTM E90-99 and E413-87

SOUND ABSORPTION COEFFICIENTS

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	NRC
QuietMOD H/P-50 PANEL	0.68	1.06	1.12	1.08	1.03	0.98	0.95 (1.05)

*All testing conducted by Riverbank Acoustical Laboratories
 *All data in accordance with ASTM C423-90a and E795-00

REVISIONS		DESCRIPTION	
DESCRIPTION	DATE	BY	CUSTOMER

DESCRIPTION		DRAWING NO.	
QuietMOD H/P-50 ACOUSTIC PANEL		QM-HP-50	
CUSTOMER	SCALE	DRAWN BY	SHEET
		MAH	
DATE			

Noise Barriers, LLC

2001 Kelley Court, Libertyville, IL 60048
 Phone: 847-843-0500
 Fax: 847-843-0501
 www.noisebarriers.com