

QuietSwing Sound Control Doors

Door Hardware - Panic Devices

VON DUPRIN® 9875/9975 Mortise Lock Device



575 Strike

9875/9975 mortise lock device for all types of single or double doors, UL listed for Panic Exit Hardware. Devices are ANSI A156.3 – 2001 Grade 1. Fits stock hollow metal doors with 86 cutout and door stiles as narrow as 4 3/4" (121mm). The 9875 device has a smooth mechanism case and the 9975 device has a grooved case. The mortise lock device is non-handed except when the following device options are used: -2 (Double Cylinder) or SS (Signal Switch). See Opposite page for available outside trim and device functions.

The 9875/9975 devices are available in the following finishes: US3, US4, US10, US26, US26D, US28, 313AN, 315AN and US32D for the 9875 device only. See page 52 for component finishes and the inside cover for finish chips.

The 7500 Mortise lock is equipped with a 3/4" (19mm) anti-friction latch bolt which is field reversible without removing the lock from the door. It has a non-handed auxiliary bolt for deadlocking and a faceplate with an adjustable bevel.

Specifications



Device Functions	Device ships EO/DT/NL. Field selectable. For TP,K, or L adjust NL drive screw in mortise lock		
Device Lengths	3'	2'4" to 3' (711mm to 914 mm)	Door Size
	4'	2'10" to 4' (864 mm to 1219 mm)	Door Size
Strikes	575 – Dull Black Optional Strikes – see page 39		
Dogging Feature	Hex key dogging standard		
Dogging Options	CD	Cylinder Dogging	see page 48
	LD	Less Dogging	see page 48
Electric Option	RX	Pushpad Monitor Switch	see page 42
	RX2	Double Pushpad Monitor Switch	see page 42
	E	Electric Locking & Unlocking	see page 44
	EL	Electric Latch Retraction	see page 43
	SS	Signal Switch	see page 43
	CX	Chexit Delayed Exit	see page 45
	ALK	Alarm Exit Kit	see page 42
Miscellaneous Options	PN	Pneumatic Latch Retraction	see page 48
	-2	Double Cylinder	see page 48
	GBK	Glass Bead Kit	see page 49
Fasteners & Sex Bolts (SNB)	Includes 1 3/4" (19mm) – 2 1/4" (57mm) Wood & Metal Doors Optional SNB available for device, see next page for quantities		
Device Centerline from Finished Floor	39 5/8" (1006 mm)		
Center Case Dimensions	8" x 2 3/4" x 2 3/8" (203mm x 70mm x 60mm)		
Mechanism Case Dimensions	2 1/4" x 2 1/4" (57mm x 57mm)		
Projection	Pushbar Neutral – 3 13/16" (97 mm)		



QuietSwing Sound Control Doors

Door Hardware - Panic Devices, Page 2

VON DUPRIN® 9875/9975 Mortise Lock Device Standard Trim

	Exitonly	Lever Key Locks & Unlocks 	NightLatch Key Retracts Latchbolt 
Product Description	9875EO 9975EO	9875L 9975L	9875NL 9975NL
Trim Description	—	996L-M	990NL-M
Escutcheon Plate Size	—	2 ³ / ₄ " x 10 ³ / ₄ " x 2 ⁷ / ₃₂ " (70x273x21mm)	3" x 14 ¹ / ₁₆ " x 3 ³ / ₃₂ " (76x360x2mm)
Pull Center to Center	—	—	5 ¹ / ₂ " (140mm)
Projection	—	2 ¹ / ₈ " (73mm)	2" (51mm)
ANSI Function	01	08	03
Cylinder Type	—	1 ¹ / ₄ " Mortise	1 ¹ / ₄ " Mortise
Optional Trim (See pages 32 – 34)	x990EO x992EO x994EO x996EO	x992L x994L	x991K-NL x992L-NL x994L-NL x996L-NL x696NL x697NL
Optional #425 Sec Bolt Quantity for Device	6	2	2